

Specifications

PRODUCT NAME: ACETONE

| ANALYSIS ITEMS | Unit | INDEX | TEST METHOD |
|--------------------------------|---------|-------------|-------------|
| PURITY | %(M/M) | 99.5MIN | GC |
| WATER CONTENT | %(M/M) | 0.3MAX | ASTM D1364 |
| ACIDITY AS ACETIC ACID | %(M/M) | 0.002MAX | ASTM D1613 |
| POTASSIUM PERMANGANATE TIME | Minutes | 120MIN | ASTM D1363 |
| COLOR (Pt-Co) | | 10MAX | ASTM D1209 |
| APPEARANCE | | COLORLESS | VISUAL |
| NON-VOLATILE MATTER | G/100ML | 0.002MAX | ASTM D1353 |
| DIST.RANGE,(including56.1°C) | | 0.7MAX | ASTM D1078 |
| DENSITY,20°C | KG/L | 0.790-0.792 | ASTM D4052 |
| METHANOL | PPM | 500MAX | GC METHOD |
| BENZENE | PPM | 5.0MAX | GC METHOD |
| WATER SOLUBILITY | | PASS | ASTM D1722 |

For and on behalf of
 GUANGZHOU LIFLY CHEMICALS CO., LIMITED
 廣州立飛化工有限公司

Nanyou

 Authorized Signature(s)